



WATERPROOF FITTINGS

An IP65 Ingress Protection Waterproof tubes provides evidence of its dust-tightness and complete resistance to rain and jets of water.

PRODUCT FEATURES

- Luminous efficacy up to 120lm/W and 80lm/W
- Easy to install
- IP65, free from water and dirt
- Without opening the lampshade for direct wiring
- Perfect replacement for the whole set of T8 fluorescent lighting fixture
- Save up to 80% in electricity consumption compared to fluorescent lighting fixture

APPLICATIONS

Parking lots, Gas stations, Tunnels, Warehouse etc.





18W
VT-6076

N/A 3000k Warm White
6283 4500k Day White
6282 6000k White

60CM
SIZE

36W
VT-1249

N/A 3000k Warm White
6285 4500k Day White
6284 6000k White




120CM
SIZE

48W
VT-1574

N/A 3000k Warm White
6287 4500k Day White
6286 6000k White

150CM
SIZE

Model No.	VT-6076	VT-1249	VT-1574
Watts	18W	36W	48W
EQ. Watts	100W	200W	250W
Voltage/Frequency	AC:220-240V,50Hz	AC:220-240V,50Hz	AC:220-240V,50Hz
Luminous Flux	1440lm	2880lm	3840lm
LED Type	SMD	SMD	SMD
CRI	>70	>70	>70
PF	>0.5	>0.9	>0.9
Beam Angle	120	120	120
Body Type	ABS+PC	ABS+PC	ABS+PC
IP Rating	IP65	IP65	IP65
Dimension	600 x 86 x 70mm	1200 x 86 x 70mm	1500 x 86 x 70mm



EAN Code 3000K
EAN Code 4500K
EAN Code 6000K

N/A
3800157616478
3800157616461

N/A
3800157616492
3800157616485

N/A
3800157616515
3800157616508



36W
VT-1248

N/A 3000K Warmwhite
6200 4500K Daywhite
6201 6000K White

120CM
SIZE

IP65
TESTED & APPROVED



48W
VT-1548

N/A 3000K Warmwhite
6184 4500K Daywhite
6185 6000K White

150CM
SIZE

IP65
TESTED & APPROVED

Model No.

Watts

EQ. Watts

Voltage/Frequency

Luminous Flux

LED Type

CRI

PF

Beam Angle

Body Type

IP Rating

Dimension

VT-1248

36W

120W

AC:200-240V,50Hz

2800lm

SMD

>70


>0.9

120°D

Plastic

IP65

1200 x 86 x 72mm



VT-1548

48W

90W

AC85-265V/50-60Hz

4000lm

SMD

>75


>0.9

120°D

Plastic

IP65

1480 x 86 x 72mm



EAN Code 3000K
EAN Code 4500K
EAN Code 6000K

N/A
3800157603270
3800157603287

N/A
3800157602389
3800157602396



60W
VT-1260 SMD

N/A 3000K Warmwhite
6179 4500K Daywhite
6062 6000K White

120CM
SIZE

IP65
TESTED & APPROVED

120⁺⁺
LM/W
HIGH
LUMENS



70W
VT-1573

N/A 3000k Warm White
6266 4500k Day White
6267 6000k White

150CM
SIZE

IP65
TESTED & APPROVED

120⁺⁺
LM/W
HIGH
LUMENS

CM Input Current (AC240V) 20-30MA
Charging Time ≥24 Hours
Working Time ≥3 HOURS
Battery Capacity 2.2AH(2200MAH) 7.2V



LED EMERGENCY LIGHT
WITH BUILT-IN BATTERY PACK




58W
VT-558

N/A 3000K Warmwhite
7028 4500K Daywhite
7029 6000K White

120°
BEAM ANGLE

IP66

Model No.	VT-1260	VT-1573	VT-558
Watts	60W	70W	58W
EQ. Watts	500W	600W	N/A
Voltage/Frequency	AC: 200-240V, 50Hz	AC:200~240V, 50/60Hz	AC: 220-240V, 50/60Hz
Luminous Flux	7200lm	8400lm	5000lm
LED Type	SMD	SMD	SMD
CRI	>70	>70	> 80
PF	> 0.9	> 0.9	>0.9
Beam Angle	120°D	120°D	120°D
Body Type	Plastic + Aluminium	Plastic + Aluminium	IP66
IP Rating	IP65	IP65	Plastic Clad Aluminium
Dimension	1200 x 86 x 70mm	1500 x 86 x 70mm	1565 x 130x 92mm



EAN Code 3000K
EAN Code 4500K
EAN Code 6000K

N/A
3800157601610
3800230625212

NA
3800157612586
3800157612593

N/A
3800157603614
3800157603621